

ViewSonic® P76f+B 17" CRT Display

The best choice of professional display



17" Perfect Flat CRT monitor

With its PerfectFlat® screen, the black 17" ViewSonic P76f+B makes a decidedly elegant impression. Thanks to UltraBrite™ technology, perfect viewing for varying applications is assured. A simple press of the UltraBrite hot key returns extra-rich, saturated images from video, DVD, TV and games. Normal brightness for everyday applications such as word-processing and spreadsheets is restored at another touch of the button. This model boasts high resolution and is TCO'03 certified to meet strict demands for ergonomics and recyclability. Whether for general day-to-day applications or CAD/CAM professional design, the versatile P76f+B is a top choice.



Brilliant images, brilliant choice.

••• UltraBrite technology

UltraBrite monitors facilitate optimised viewing for video and graphics applications. Games, videos, TV shows and DVD movies come alive with rich, vivid colour and brightness of up to 500 nits.

••• UltraBrite Hot Key

Toggle through 3 brightness modes with a touch of a button.

••• PerfectFlat® screen

Absolutely flat screen surface provides realistically proportioned, precise images with reduced reflection, image distortion and eye fatigue.

••• ViewPS-The Advanced Energy Saving CRT Technology

ViewPS technology can reduce power consumption for 14.4 to 19.2 watts depending on usages like word processing, gaming, or entertainments, saving almost 20% on electricity bills.

••• TCO'03, RoHS, and Energy Star certified

••• 2048 X 1536 maximum resolution

The maximum resolution is 2048 x 1536 at 60Hz refresh rate for easy-on-the eyes viewing. For comfortable viewing, 1280 x 1024 at a flicker-free refresh rate of 89Hz is recommended.

2048 X 1536 @ 60 Hz

1920 X 1440 @ 64Hz

1792 X 1344 @ 68 Hz

1600 X 1200 @ 77 Hz

1280 X 1024 @ 89 Hz

1024 X 768 @ 118 Hz

800 X 600 @ 148Hz

640 X 480 @ 160Hz

••• ViewCare Technology

ViewSonic's exclusive ViewCare new-generation CRT technology can produce healthy anion and far infrared ray with "Vital C/T" and "Pure C/T" coating treatments

Big Screen

ViewSonic® 

the choice of professionals

ViewSonic® P76f+B 17" CRT Display

The best choice of professional display

Model No.VS11262



Resolution :

2048 × 1536@60Hz
1920 × 1440@64Hz
1792 × 1344@68Hz
1600 × 1200@77Hz
1280 × 1024@89Hz
1024 × 768@118Hz
800 × 600@148Hz
640 × 480@160Hz

CRT	Type	17" (16"viewable)
	Dot Pitch	0.25mm Diagonal 0.20mm Horizontal 0.13mm Vertical
	Glass Surface	Anti-Static, Anti-Reflection
INPUT	Video	RGB Analog (75 ohms, 0.7/1.0Vp-p)
	Sync	H/V Separated(TTL), Composite Sync
	Frequency	Fh:30-97kHz, Fv:50-160Hz
COMPATIBILITY	PC	VGA up to 2048 × 1536@60Hz
	Mac	Power Mac (*May requires Mac cable adapter)
CONNECTOR	Singal	15 pin mini D-sub
	Power	3 pin plug (IEC320)
	Voltage	AC 90-264VAC (auto switch) 50/60(+/-) Hz
	Consumption	<54W Typ.
CONTROLS	Basic	Key-1, Up, Down, Key-2, Power on/off,
	OnView	Contrast, Brightness, Degauss, H. Size/Position, V. Size/Position, Zoom, Pincushion, Pinbalance, Trapezoid, Parallelogram, Tilt, Moir_ Reduction, ViewMatch (9300, 6500, 5000, User), Language, ViewMeter, OSD, Position, Zoom, Recall
VIDEO INPUT	Bandwidth	260MHz
MISCONVERGENCE	A zone	0.25mm (max) at center
	B zone	0.35mm (max) at corner
DISPLAY AREA	Factory Setting	310mm × 230mm
	Maximum Scan	320mm × 240mm (Dependent upon signal timing used)
OPERATING CONDITIONS	Temperature	0°C-40°C (32°F-104°F)
	Humidity	5%-95% (non-condensation)
DIMENSIONS (W×D×H)	Physical	410mm × 424mm × 405.5mm (With Base) 16.1" × 16.5" × 15.96" (With Base)
	Weight	15 Kgs (33.1 lbs)
REGULATIONS		MPR-II, TCO03, EPA Energy Star tier-II, CCC, BSMI, PSB

specifications

Headquarters:

381 Brea Canyon Road,
Walnut, CA 97189, U.S.A.
Tel:(909)898-8683 (909)444-8888
Fax:(909)839-7922
www.viewsonic.com

Asia Pacific:

9F, No. 192 Lien Chien Road,
Chung Ho, Taipei, R.O.C.
Tel:886-2-2246-3456
Fax:886-2-6242-3666
www.viewsonic.com.tw

ViewSonic Hong Kong

Unit 3, 15/F, Greenfield Tower,
Concordia Plaza, 1 Science Museum Road,
TST East, Kowloon, Hong Kong
Tel:002-852-3690-1398 or #17
Fax:002- 852-3690-1399
www.hk.viewsonic.com

ViewSonic (Singapore) Pte Ltd

221 Henderson Road #04-06
Henderson Building
Singapore 159557
Tel:+65-6273-4018
Fax:+65-6273-1566
www.viewsonic.com.sg

ViewSonic Australia Pty Ltd

Unit 3, 44 Dickson Avenue,
Artarmon NSW 2064,
Australia
Tel:(02)9906-6277
Fax:(02)9906-6377
www.viewsonic.com.au



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

For more product information, visit us on the web at ViewSonic.com

20060616