

# VA2012wb

## 20.1" DIGITAL MULTIMEDIA WIDE-SCREEN LCD DISPLAY

WITH 8MS CLEARMOTIV™ HD BROADCAST-QUALITY VIDEO

## Tantalizing visual experience.

The ViewSonic® VA2012wb 20.1" LCD is packed with an IMPRESSIVE ARRAY OF FEATURES TO ENHANCE YOUR WORK AND PLAY, and the budget-friendly price makes it an even more tantalizing package. The 16:10 wide-screen aspect ratio provides more productive space for multiple windows, HD-format video and immersive gaming action. This feature-rich display includes ViewSonic's innovative Dynamic Structure™ technology and ClearMotiv™ 8ms video response for SEAMLESS VIDEO AND INTENSE GRAPHICS. The 300 nits of brightness (typ), 600:1 contrast ratio (typ), and 1680x1050 optimum resolution ensure crystal-clear images and crisp text. Mount the VA2012wb on your wall and save valuable desktop real estate. It's a stylish wide-screen LCD that upgrades your workspace while staying within your budget.

**It's not just another wide-screen LCD. It's a ViewSonic.**



### AFFORDABLE PERFORMANCE WITHOUT COMPROMISE

- > **Wide-screen experience**  
Wide-format screen is ideally suited to maximize natural field of vision for intense game play, HD format video, and multiple document windows.
- > **ClearMotiv™ technology**  
Fast 8ms video response enables digital HD-quality full motion video.
- > **Dynamic Structure™ technology**  
Innovative liquid crystal composition and pixel matrix accelerate video response at frame rates up to 125 fps for seamless video and intense graphics.
- > **High brightness and contrast**  
300-nit brightness (typ) and 600:1 contrast ratio (typ) for rich, detailed images.
- > **OSD/power lock secures your settings**  
Prevents changes to monitor settings and maintains an optimized image.
- > **Full 20.1" viewable wide screen with 16:10 aspect ratio**
- > **1680x1050 native resolution**
- > **Stylish slim-bezel design**
- > **OnView® controls for superior screen adjustability**
- > **Integrated power supply**
- > **PC and Mac® compatible**
- > **TCO'99 and ENERGY STAR® certified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic** 

*the choice of professionals*

# VA2012wb

## 20.1" DIGITAL MULTIMEDIA WIDE-SCREEN LCD DISPLAY WITH 8MS CLEARMOTIV™ HD BROADCAST-QUALITY VIDEO



<b>LCD</b>	Type	20.1" color TFT active matrix SXGA LCD
	Display Area	17.1" horizontal x 10.7" vertical; 20.1" diagonal
	Optimum Resolution	1680x1050
	Contrast Ratio	600:1 (typ)
	Viewing Angles	160° horizontal, 145° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Aspect Ratio	16:10
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog/Digital	RGB analog (75 ohms, 0.7/1.0 Vp-p)/DVI-D (TMDS, 100 ohms)
	Analog Frequency	F <sub>H</sub> : 30~94kHz, F <sub>V</sub> : 50~75Hz
	Digital Frequency	F <sub>H</sub> : 30~82kHz, F <sub>V</sub> : 50~75Hz
	Sync	H/V separated (TTL)
<b>AUDIO</b>	Speakers	Dual integrated stereo speakers
<b>COMPATIBILITY</b>	PC	VGA up to 1680x1050 non-interlaced
	Mac®*	Power Mac™ G3/G4/G5 up to 1680x1050
<b>CONNECTOR</b>	Analog/Digital	15-pin mini D-sub/DVI-D
	Power	3-pin AC plug (CEE22)
	Audio-In	Stereo mini audio line in
<b>POWER</b>	Voltage	AC 100–240V, 50/60Hz
	Consumption	47W (typ)
<b>CONTROLS</b>	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, contrast, brightness, input select, audio adjust, ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, user color RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number, web site), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
<b>OPERATING CONDITIONS</b>	Temperature	32–104°F (0–40°C)
	Humidity	10–90% (non condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical (mm)	479mm x 423mm x 216mm
	Physical (in.)	18.9" x 16.7" x 8.5"
<b>WEIGHT</b>	Net	12.1 lb. (5.5 kg)
	Gross	15.4 lb. (7.0 kg)
<b>REGULATIONS</b>		UL, cUL, FCC-B, CB, CE, NOM, TUV/Ergo, ICES-003, TUV/GS, (covers ISO 13406-2 and MPR II), TCO'99, GOST-R, SASO, PCBC, TUV-S, BSMI, CCC, ENERGY STAR®, PSB, C-TICK, Green Mark, MIC
<b>POWER MANAGEMENT</b>		Meets TCO'99 and ENERGY STAR® standards
<b>PACKAGE CONTENTS</b>		LCD display, DVI cable, VGA cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789  
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. [12657-00B-10/05] VA2012wb-1

**ViewSonic** 

*the choice of professionals*

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)