

# VA1716w

## 17" VALUE SERIES WIDESCREEN LCD

WITH 8MS VIDEO RESPONSE

## Budget-friendly widescreen.

ViewSonic's 17" VA1716w LCD brings widescreen performance to budget-conscious users. The 16:10 aspect ratio and high 1440x900 resolution allow you to view two documents side-by-side or to WORK IN MULTIPLE APPLICATIONS SIMULTANEOUSLY. PC gamers will appreciate the immersive gaming action delivered by fast ClearMotiv® video response. You'll be amazed by the EXTREME CLARITY AND BRILLIANT COLORS of the VA1716w. This widescreen LCD features a stylish chassis that complements any desktop while delivering brilliant image quality and reliable performance all at an appealing price point. It's the easy choice for gamers, home/small office users and corporate professionals.



### MORE PRODUCTIVITY. MORE FUN.

- > **Fast 8ms video response** delivers superior picture clarity
- > **Full 17" viewable widescreen**  
Displays a full, flat 17" viewable area with crisp detail and fully saturated color.
- > **1440x900 native resolution**  
Incredible image detail for sharp text and graphics.
- > **High brightness and contrast ratio**  
250-nit brightness (typ) and 500:1 contrast ratio (typ) for rich, detailed images.
- > **Stylish slim-bezel design**  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**  
Prevents changes to monitor settings and maintains an optimized image.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Windows Vista approved**
- > **ViewSonic Wizard included**  
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > **PC and Mac® compatible**
- > **MPR II and ENERGY STAR® qualified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# VA1716w

17" VALUE SERIES WIDESCREEN LCD WITH 8MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13564-01B-07/07] VA1716w-2

<b>LCD</b>	Type	17" color TFT active matrix SXGA LCD
	Display Area	14.4" horizontal x 9.0" vertical; 17.0" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	500:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 30,000 hrs. (typ)
	Brightness	250 cd/m2 (typ)
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Frequency	F <sub>H</sub> : 30~82kHz, F <sub>V</sub> : 50~75Hz
	Sync	H/V separated (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1440x900 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1440x900
<b>CONNECTOR</b>	Analog	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
<b>POWER</b>	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
	Consumption	25W (typ)
<b>CONTROLS</b>	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, contrast, brightness, ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information (resolution, H-freq, V-freq, pixel clock, model number, serial number, web site), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
<b>OPERATING</b>	Temperature	32~104°F (0~40°C)
<b>CONDITIONS</b>	Humidity	10~90% (non-condensing)
<b>DIMENSIONS</b>	Physical with stand	15.6" x 14.1" x 7.7" (398mm x 357mm x 195mm)
	Physical without stand	15.6" x 11.0" x 2.5" (398mm x 280mm x 63mm)
<b>(W x H x D)</b>		
<b>WEIGHT</b>	Net with stand	7.0 lb. (3.2 kg)
	Net without stand	6.38 lb. (2.9 kg)
	Gross with stand	9.9 lb. (4.5 kg)
<b>REGULATIONS</b>		UL, cUL, FCC-B, CB, CE, NOM, TUV/GS, TUV/ERGO (covers ISO13406-2), MPR II, BSMI, CCC, ENERGY STAR®, PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO
<b>RECYCLE/DISPOSAL</b>		The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
<b>POWER MANAGEMENT</b>		Meets MPR II and ENERGY STAR® standards
<b>PACKAGE CONTENTS</b>		LCD display, video cable, power cable, Quick Start Guide, ViewSonic Wizard
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)