

# VA1926w

## 19" VALUE SERIES WIDESCREEN LCD

WITH 5MS VIDEO RESPONSE

## Extreme widescreen clarity.

ViewSonic's 19" VA1926w LCD brings new clarity to budget-priced widescreen displays. Prepare to be amazed at this display's EXTREME CLARITY, AMAZING COLOR AND STUNNING BRIGHTNESS. With 2000:1 DYNAMIC CONTRAST RATIO (typ), 1440x900 resolution and fast ClearMotiv® 5ms video response graphics, videos and spreadsheets have never been clearer. Be more productive while viewing two full-size documents side-by-side or WORKING IN MULTIPLE APPLICATIONS SIMULTANEOUSLY on the widescreen display. With its stylish, slim bezel design and VESA® wall-mount compliance, the VA1926w fits seamlessly into any office décor. It's the right choice for home/small office users, corporate professionals and gamers.



**2000:1**  
Dynamic Contrast Ratio

### PRODUCTIVE AND ENTERTAINING

- > **Fast 5ms video response** delivers superior picture clarity
- > **Full 19" viewable widescreen**  
Displays a full, flat 19" viewable area with crisp detail and fully saturated color.
- > **1440x900 native resolution**  
Incredible image detail for sharp text and graphics.
- > **2000:1 dynamic contrast ratio (typ)**  
Provides for darker black levels and better overall front-of-screen performance.
- > **Stylish slim-bezel design**  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OptiSync® digital/analog inputs expand your connectivity**  
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **OSD/power lock secures your settings**  
Prevents changes to monitor settings and maintains an optimized image.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Windows Vista approved**
- > **ViewSonic Wizard included**  
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# VA1926w

19" VALUE SERIES WIDESCREEN LCD WITH 5MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13597-00B-07/07] VA1926w-3

<b>LCD</b>	Type	19" color TFT active matrix WSXGA LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19.0" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	700:1 static (typ), 2000:1 dynamic (typ)
	Viewing Angles	160° horizontal, 160° vertical
	Response Time	5ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
<b>VIDEO INPUT</b>	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI
<b>COMPATIBILITY</b>	Frequency	F <sub>H</sub> : 30~82kHz, F <sub>V</sub> : 50~75Hz
	Sync	H/V separated (TTL)
	PC	VGA up to 1440x900 non-interlaced
<b>CONNECTOR</b>	Mac**	Power Mac™ G3/G4/G5 up to 1440x900
	Analog/Digital	15-pin mini D-sub/Digital
<b>POWER</b>	Power	3-pin AC plug (CEE22)
	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
<b>CONTROLS</b>	Consumption	32W (typ)
	Basic	Power, 1, down, up, 2
<b>ERGONOMICS</b>	OnView®	Auto image adjust, contrast, brightness, ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
	Tilt	-5°/+20°
<b>OPERATING</b>	Temperature	32~104°F (0~40°C)
<b>CONDITIONS</b>	Humidity	20~90% (non-condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical with stand	17.3" x 15.2" x 7.7" (440mm x 383mm x 195mm)
	Physical without stand	17.3" x 12.0" x 2.4" (440mm x 304mm x 62mm)
<b>WEIGHT</b>	Net with stand	8.8 lb. (4.0 kg)
	Net without stand	7.7 lb. (3.5 kg)
	Gross with stand	11.2 lb. (5.1 kg)

**REGULATIONS** UL, cUL, FCC-B, CB, CE, NOM, TUV-S, TUV/GS, TUV/ERGO (covers ISO13406-2), MPR II, BSMI, CCC, ENERGY STAR®, PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver

**RECYCLE/DISPOSAL** The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.

**POWER MANAGEMENT** Meets TCO'03 and ENERGY STAR® standards

**PACKAGE CONTENTS** LCD display, video cable, power cable, Quick Start Guide, ViewSonic Wizard (DVI cable not included)

**WARRANTY** Three-year limited warranty on parts, labor and backlight

**ViewSonic®**  
See the difference®

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)