

# VX2250wm-LED

## 22" (21.5" VIEWABLE) LED MONITOR

WITH 10,000,000:1  
DYNAMIC CONTRAST RATIO

## Perfect package: Sleek, green, powerful.

ViewSonic's VX2250wm-LED features an environmentally friendly mercury free LED backlight, 22" (21.5" Vis) widescreen monitor with up to 40% energy saving compared to a regular 22" monitor. It offers Full HD 1920x1080 resolution, 5ms response time, 10,000,000:1 MEGA Dynamic Contrast Ratio, digital and analog inputs and integrated stereo speakers. Ideal for both home and office with the piano black finish, VX2250wm-LED can be mounted on a VESA compliant stand or wall mount bracket. It also has an automatic aspect ratio adjustment so when your input is a 4:3 signal, the image will not be stretched but instead it will be positioned in the middle of the screen with side bars. 3 year warranty, industry's best pixel performance policy and Windows 7 certification make VX2250wm-LED a great long term investment.



### GO GREEN WITH FULL POWER

- > Uses 40% less power  
Without compromising your viewing quality and has eco-friendly mercury free WLED backlight.
- > Full HD 1080p with 16:9 aspect ratio  
Achieves perfect image reproduction without distortion
- > DVI and VGA inputs for diverse connectivity
- > Integrated speakers for multimedia applications  
Save desk and workspace and enjoy rich stereo sound
- > Dynamic contrast ratio at 10,000,000:1  
For true-to-life picture depth and clarity in any room.
- > Highest grade panel  
For crisp images and the best pixel performance in the industry
- > PC and Mac® compatible
- > VESA® compliant  
100mm x 100mm VESA® mountable design



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# VX2250wm-LED

22" (21.5" VIEWABLE) LED MONITOR WITH 10,000,000:1 DYNAMIC CONTRAST RATIO



<b>LED</b>	Type	22" (21.5" Viewable) Wide Color TFT Active Matrix LCD
	Display Area	18.7" horizontal x 10.6" vertical; 21.5" diagonal
	Optimum Resolution	1920x1080p
	Contrast Ratio	1000:1 (typ); 10,000,000:1 (dynamic)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 25,000 hrs. (typ)
	Brightness	250 cd/m <sup>2</sup> (typ)
<b>VIDEO INPUT</b>	Panel Surface	Anti-glare
	Analog	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F <sub>H</sub> : 24~83kHz, F <sub>V</sub> : 50~75Hz
<b>COMPATIBILITY</b>	Sync	H/V separated (TTL), composite sync-on-green
	PC	VGA up to 1920x1080 non-interlaced
<b>CONNECTOR</b>	Mac®*	Power Mac™ G3/G4/G5 up to 1920x1080
	Analog	15-pin mini D-sub (VGA)
<b>AUDIO</b>	Digital	DVI-D
	Power	3-pin AC plug (CEE22)
<b>POWER</b>	Speakers	2x2-watt
	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
<b>CONTROLS</b>	Consumption	26W (typ)
	Basic	Power, 1, down, up, 2
<b>ERGONOMICS</b>	OSD	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K, 5400K, default, user color - RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
	Tilt	Down 5°, Up 20°
<b>OPERATING</b>	Temperature	32~104° F (0~40° C)
<b>CONDITIONS</b>	Humidity	20~90% (non-condensing)
<b>DIMENSIONS</b> (W x H x D)	Physical with stand	20.5" x 15.9" x 7.5" (521mm x 404mm x 190mm)
	Physical without stand	20.5" x 12.7" x 1.8" (521mm x 340mm x 49mm)
	Packaging	22.7" x 19.7" x 5.2" (569.1mm x 495mm x 126mm)
<b>WEIGHT</b>	Net with stand	7.5 lb. (3.4 kg)
	Net without stand	7.1 lb. (3.2 kg)
	Gross	10.4 lb. (4.7 kg)
<b>VESA® MOUNT</b>		100mm x 100mm
<b>REGULATIONS</b>		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, GS (covers GS), ERGO (ISO13406-2 & MPR II), MPR II, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, MIC (KCC), WEEE, RoHS, EPEAT Silver
<b>POWER MANAGEMENT</b>		Meets MPR II and ENERGY STAR® standards
<b>PACKAGE CONTENTS</b>		LCD display, power cable, VGA video cable, DVI cable, audio cable, Quick Start Guide, ViewSonic Wizard CD (User Guide and drivers)
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight.



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14938-00B-04/10] VX2250wm-LED

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at ViewSonic.com