



PROXIMITY CARD READER

FEATURES

- Elegant black PVC body gives a sturdy and professional look
- Unobstrusive Design can be mounted directly on to Metal
- Audio Visual Indication
- Widely used in high security zones
- User friendly installation
- Available with Weigand Output
- USB port for ease in data storage/transfer/backup
- Versatile interface options
- Instant verification and enrollment
- Multi user / admin facility
- Tamperproof
- Quality tested
- Best suited for SOHO's, commercial establishments and schools

Model No. ZXRAKWP

Storage	Card Holders	30000 Cards
	Transaction Capacity	50000 records
Operation	CPU	64 bit Microprocessor
	Hardware	Embedded Linux O/S
	Operating Temperature	0° C ~ 45° C
	Operating Humidity	20% ~ 80%
	Housing Material	ABS
	Power Requirement	12V DC, 400 mA
Card Options	Card Only, Pin Only, Card+Pin	
Communication	I/O interface	RS 232 (10m) / RS 485 (1.2Km)
	Baud Rate	9600 - 115 Kbps programmable
	Ethernet	10 / 100 M TCP / IP
	Weigand Output	Any bit
	Weigand Input	Any bit
	USB	Mini - USB 2.0 port
Multimedia	Read Range	10 - 15 cm
	LCD Panel	4 line, 16 character each line (User name, ID number, time, date, states)
	Keypad	4 x 4 metal keypad with 4 function keys
	Audio Visual Indicator	Red Led
Access Control Function	Time Zones	50
	Groups	5
	Open Door Communication	10
	Outputs	TTL for connection to lock, Door Sensor, Exit Button, Alarm